



WALLA WALLA ENVIRONMENTAL, INC.

FLOC-720™

Anionic flocculant

Discover the benefits of our entire family of products for process water treatment:

- CAT-30
- CAT-34
- CAT-90
- FLOC-600
- FLOC-720
- Stat-125
- pH Adjust and Chemical Sludge Conditioner
- Metal Precipitant
- DE
- Clean-In-Place I Cleaner
- Clean-In-Place II Filter Cleaner
- Biocides
- Cleaners
- Specialty Products

Description: W2E FLOC-720 is a water-based medium molecular weight anionic flocculant (polymer) designed for use in a variety of industrial wastewater treatment applications. FLOC-720 is especially effective as a coagulant aid. The product increases floc size and density improving sedimentation and sludge dewatering characteristics.

Physical Data:

Appearance	Clear amber liquid
Specific Gravity	1.02
pH	6-8
Flash Point	>200°F (93°C) product not combustible

Feed Rate: FLOC-720 feed rates range from 100 to 1,000 ppm. For a more accurate determination of usage rates, contact your Walla Walla Environmental sales consultant.

Feed Method: FLOC-720 can be fed directly from the shipping container into an area with good mixing. There is no need for dilution. The product should be fed through an appropriately sized chemical feed pump with a high viscosity pump-head. Suitable materials of construction include: Stainless Steel, Polyethylene, Polypropylene, PVC, Teflon, Kynar or Polystyrene. In some cases, aluminum and galvanized surfaces can be adversely affected.

Packaging: FLOC-720 is available in 55-gallon drums, 275 and 330-gallon totes.

*Technical data
continued on next page*

ENVIRONMENTAL, INC.
P.O. Box 1298
Walla Walla, WA 99362
www.wwenvironmental.com

TOLL FREE CUSTOMER SERVICE
800-247-9011

W2E 720
Technical data,
continued

Storage: W2E 720 should be kept in a warm, dry place and conditions of extreme temperatures should be avoided. Drums should be kept sealed when not in use. W2E 720 has a six month shelf life.

Spills: W2E 720 should be contained and disposed in accordance with local regulations. Discharges of product to waterways should be avoided since some polymeric products may have an adverse effect on the mucous membranes on fish gills.

Health and Safety: W2E 720 exhibits a very low order of toxicity and does not present any abnormal problems in its handling or general use. Standard industrial safety procedures should be observed.

Important: Read and follow carefully all directions supplied by Walla Walla Environmental. Walla Walla Environmental warrants that this material is reasonably fit for the purposes stated in our literature when used in accordance with our written and verbal directions. Under no circumstances shall Walla Walla Environmental be liable for incidental consequential or other damages from alleged negligence, breach of warranty, strict liability or any other theory arising out of the use or handling of this product. Neither this warranty nor any other warranty of merchant or fitness of purpose, neither express or implied, extends to the use of this material contrary to our directions, or under conditions not reasonably foreseeable by Walla Walla Environmental.

WALLA WALLA
ENVIRONMENTAL, INC.
P.O. Box 1298
Walla Walla, WA 99362
www.wwenvironmental.com

TOLL FREE CUSTOMER SERVICE
800-247-9011
