



METAL PRECIPITANT™

Discover the benefits of our entire family of products for process water treatment:

- CAT-30
- CAT-34
- CAT-90
- FLOC-600
- FLOC-720
- Stat-125
- pH Adjust and Chemical Sludge Conditioner
- Metal Precipitant
- DE
- Clean-In-Place I Cleaner
- Clean-In-Place II Filter Cleaner
- Biocides
- Cleaners
- Specialty Products

Description: W2E METAL PRECIPITANT is a 40% aqueous solution of an organic sulfide. The product is designed for use in industrial applications to precipitate low concentrations of heavy metals in situations where conventional treatment is inadequate.

W2E METAL PRECIPITANT is especially effective in industrial applications where metals are heavily complexed or chelated. It is typically fed in conjunction with an AC series coagulant and AP series flocculant in order to increase sludge density and sedimentation.

Physical Data:

Appearance:	yellow-green to amber
pH (neat) :	11.5 - 12.0
Specific gravity (@77°F):	1.17
Solubility in water:	complete
Freeze point:	20°F

Feed Rate: W2E METAL PRECIPITANT feed rates will range from 50 to 1,000 ppm. For a more accurate determination of usage rates, consult your Walla Walla Environmental sales consultant.

Feed Method: W2E METAL PRECIPITANT can be fed neat directly from the shipping container into an area with good mixing. The product should be fed through any appropriately sized chemical feed pump with suitable materials of construction including; Polyethylene, Polypropylene, PVC, Teflon, Kynar or Polystyrene. Stainless steel and carbon steel are not recommended.

Packaging: W2E METAL PRECIPITANT is available in 55-gallon drums, totes and bulk.

*Technical data
continued on next page*

METAL PRECIPITANT
Technical data,
continued

Handling: Do not take internally. In case of contact with skin, flush promptly and thoroughly with clear water for 15 minutes. Should be handled as any corrosive material. Rubber gloves and apron are recommended when handling this material.

Storage: Storage for more than six months is not recommended. Keep container tightly closed. Do not store near combustible materials. W2E METAL PRECIPITANT should be stored at moderate temperatures (40° - 85°F).

Important: Read and follow carefully all directions supplied by Walla Walla Environmental. Walla Walla Environmental warrants that this material is reasonably fit for the purposes stated in our literature when used in accordance with our written and verbal directions. Under no circumstances shall Walla Walla Environmental be liable for incidental consequential or other damages from alleged negligence, breach of warranty, strict liability or any other theory arising out of the use or handling of this product. Neither this warranty nor any other warranty of merchant or fitness of purpose, neither express or implied, extends to the use of this material contrary to our directions, or under conditions not reasonably foreseeable by Walla Walla Environmental.

WALLA WALLA
ENVIRONMENTAL, INC.
P.O. Box 1298
Walla Walla, WA 99362
www.wwenvironmental.com

TOLL FREE CUSTOMER SERVICE
800-247-9011
